

Sinico Sin-O-Matic TOP2000 Twin Spindle CNC Cutting Machine



SINICO TOP 2000CSV Twin Opposed Spindle Milling, Drilling and Cut to Length System
Model: Sin-O-Matic TOP2000CSV

- **Stock Number:** AM21002
- **Capacity:** 80 mm

Specifications (per mfg literature):

- Maximum Capacity: 3.5"OD (90mm)
- Minimum Capacity: 1.18"OD (30mm)
- Maximum cut length: 13.39" (340mm)
- Maximum bar/tube length: 255.9" (6,500mm)
- Minimum bar/tube length: 118.1" (3000mm)
- Cutting Speed: 40-267 m/min
- Blade Speed: 35-230 rpm
- Blade Diameter: 14.5" (370mm)

- Spindle Speed: 550-3000 rpm
- Spindle feed speed: 0-4m/min
- Spindle stroke: 3.14" (80mm)
- Tool-holder shank: ISO 40

Includes:

- Multi-Axis CNC Controls
- Touchscreen for programming and machine set-up
- Encoder for accurate material feeding
- 6-Station rotary part transfer for end-finishing operations
- Automatic machine and saw lubrication
- Infeed rack/debundler
- Chip conveyor
- Outfeed conveyor